



VB Baler Specifications and Dimensions

(800) 678-7320

sales@jv.com

| Cram-A-Lot VB Series SPECIFICATIONS | | VB-42-SR | VB-46-LD | VB-42-B | VB-60-SR | VB-60-B | VB-60-B-C | VB-60-B-LP | VB-60-H | VB-60-T | VB-60-X | VB-72-B | VB-72-B-LP | VB-72-H | VB-72-H-DC | VB-72-H-LP | VB-72-T | VB-72-X |
|-------------------------------------|-----------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| Nominal Bale Size | Width | 42" | 46" | 42" | 60" | 60" | 60" | 60" | 60" | 60" | 60" | 72" | 72" | 72" | 72" | 72" | 72" | 72" |
| | Depth | 24" | 24" | 30" | 30" | 30" | 30" | 30" | 30" | 30" | 30" | 30" | 30" | 30" | 42" | 30" | 30" | 30" |
| | Height | 28" | 36" | 48" | 30" | 48" | 48" | 38" | 48" | 48" | 48" | 48" | 48" | 48" | 48" | 38" | 48" | 48" |
| Bale Weight Up To (OCC) | | 200 lbs | 400 lbs | 750 lbs | 600 lbs | 1,000 lbs | 1,000 lbs | 900 lbs | 1,400 lbs | 1,200 lbs | 1,400 lbs | 1,200 lbs | 950 lbs | 1,600 lbs | 1,700 lbs | 1,250 lbs | 1400 lbs | 1,600 lbs |
| Cycle Time (Average) | | 23 sec | 39 sec | 57 sec | 43 sec | 56 sec | 56 sec | 45 sec | 77 sec | 56 sec | 60 sec | 57 sec | 45 sec | 77 sec | 77 sec | 59 sec | 56 sec | 60 sec |
| Cycle Time w/ Regen Option | | N/A | N/A | 34 sec | n/a | 33 sec | 33 sec | 27 sec | 44 sec | 33 sec | 35 sec | 34 sec | 33 sec | 44 sec | 44 sec | 35 sec | 33 sec | 35 sec |
| Platen Force | | 23,545 lbs | 31,800 lbs | 59,370 lbs | 59,370 lbs | 59,370 lbs | 59,370 lbs | 59,370 lbs | 92,350 lbs | 67,850 lbs | 92,350 lbs | 59,370 lbs | 59,370 lbs | 92,350 lbs | 92,450 lbs | 92,350 lbs | 67,850 lbs | 92,350 lbs |
| Platen Face Pressure | | 32 psi | 41 psi | 48 psi | 48 psi | 48 psi | 48 psi | 48 psi | 75 psi | 55 psi | 75 psi | 48 psi | 48 psi | 75 psi | 43 psi | 61 psi | 45 psi | 61 psi |
| Motor - 3 Phase 208/230/460 VAC | | 5 hp | 5 hp | 10 hp | 10 hp | 10 hp | 10 hp | 10 hp | 15 hp | 15 hp | 20 hp | 10 hp | 10 hp | 15 hp | 15 hp | 15 hp | 15 hp | 20 hp |
| Motor - 1 Phase 230 VAC | | 5 hp | 5 hp | 5 hp | 5 hp | 5hp | 5hp | 5hp | N/A | N/A | N/A | 5hp | 5hp | N/A | N/A | N/A | N/A | N/A |
| Pump Capacity | | 6 gpm | 6 gpm | 9 gpm | 9 gpm | 9 gpm | 9 gpm | 9 gpm | 10.5 gpm | 10.5 gpm | 13.5 gpm | 9 gpm | 9 gpm | 10.5 gpm | 10.5 gpm | 10.5 gpm | 10.5 gpm | 13.5 gpm |
| Hydraulic Reservoir Capacity | | 11 gal | 11 gal | 30gal | 30 gal | 30gal | 30gal | 30gal | 30gal | 30gal | 30gal | 30gal | 30gal | 30gal | 30gal | 30gal | 30gal | 30gal |
| Hydraulic Cylinder | Bore Dia. | (two) 3" | 4 1/2" | 6" | (two) 5" | 6" | 6" | 6" | 7" | 6" | 7" | 6" | 6" | 7" | 7" | 7" | 6" | 7" |
| | Stroke | 36" | 36" | 44" | 23" | 44" | 44" | 34" | 44" | 52" | 52" | 44" | 44" | 34" | 52" | 38" | 52" | 52" |
| | Rod Dia. | 1 3/8" | 2 1/2" | 3.5" | 3" | 3 1/2" | 3 1/2" | 3 1/2" | 4" | 4" | 4" | 3 1/2" | 3 1/2" | 4" | 4" | 4" | 4" | 4" |
| Operating Pressure | | 2,000 psi | 2,000 psi | 2,100 psi | 2000 psi | 2,100 psi | 2,100 psi | 2,100 psi | 2,100 psi | 2,400 psi | 2,400 psi | 2,100 psi | 2,100 psi | 2,100 psi | 2,400 psi | 2,100 psi | 2400 psi | 2,400 psi |

| Cram-A-Lot VB Series DIMENSIONS | Overall Height Installed | Frame Height | Overall Width | Overall Depth with Door Closed | Overall Depth with Door Open | Loading Height | Feed Opening Height | Unit Weight |
|---------------------------------|--------------------------|--------------|---------------|--------------------------------|------------------------------|----------------|---------------------|-------------|
| VB-42-SR | 6' 7" | 6' 6" | 5' 3 1/2" | 2' 11" | 6' 3" | 34 1/2" | 23" | 2,550 lbs |
| VB-46-LD | 9' 9" | 6' 11" | 5' 8" | 3' 1" | 6' 9" | 42" | 24" | 2,750 lbs |
| VB-42-B | 11' 8" | 8' 3" | 5' 5" | 3' 7" | 6' 11" | 52" | 23" | 3,850 lbs |
| VB-60-B | 11' 8" | 8' 3" | 6' 11" | 3' 7" | 8' 5" | 52" | 24" | 4,450 lbs |
| VB-60-B-C | 11' 8" | 8' 3" | 6' 11" | 3' 7" | 8' 5" | 52" | 24" | 4,450 lbs |
| VB-60-B-LP | 9' 11" | 7' 5" | 6' 11" | 3' 7" | 8' 5" | 42" | 24" | 4,100 lbs |
| VB-60-H | 12' 4" | 8' 3" | 6' 11" | 3' 7" | 8' 5" | 52" | 24" | 5,000 lbs |
| VB-60-T | 12' 4" | 8' 3" | 6' 11" | 3' 7" | 8' 5" | 52" | 24" | 4,800 lbs |
| VB-60-X | 12' 4" | 8' 3" | 6' 11" | 3' 7" | 8' 5" | 52" | 24" | 5,050 lbs |
| VB-60-SR | 6' 9" | 6' 9" | 6' 11" | 3' 7" | 8' 5" | 35 1/2" | 24" | 4,200 lbs |
| VB-72-B | 11' 8" | 8' 3" | 7' 11" | 3' 7" | 12' 5" | 52" | 24" | 4,850 lbs |
| VB-72-B-LP | 19' | 7' 5" | 7' 11" | 3' 7" | 12' 5" | 42" | 24" | 4,520 lbs |
| VB-72-H | 12' 4" | 8' 3" | 7' 11" | 3' 7" | 12' 5" | 52" | 24" | 5,450 lbs |
| VB-72-H-DC | 12' 4" | 8' 3" | 7' 11" | 4' 7" | 10' 5" | 52" | 24" | 6,200 lbs |
| VB-72-H-LP | 12' 4" | 7' 5" | 7' 11" | 3' 7" | 12' 5" | 42" | 24" | 5,000 lbs |
| VB-72-T | 12' 4" | 8' 3" | 7' 11" | 3' 7" | 12' 5" | 52" | 24" | 5,200 lbs |
| VB-72-X | 12' 4" | 8' 3" | 7' 11" | 3' 7" | 12' 5" | 52" | 24" | 5,500 lbs |